

DEHUMIDIFIER PRODUCT RANGE

1 YEAR
WARRANTY



DP
DEHUMIDIFIER

DN
DEHUMIDIFIER

DF
DEHUMIDIFIER



**DP
DEHUMIDIFIER**
DP 30 - DP 50

PRODUCT FEATURES & DESCRIPTION

• COMFORT

• SMART DEHUMIDIFICATION:

Automatically control room humidity in a comfortable range of 45% ~ 55% according to room temperature, inhibiting bacterial growth.

• LOW-NOISE DESIGN:

Minimize noise and maximize comfort by optimizing the refrigeration and air duct systems.

• AUTO-DEFROSTING FUNCTION:

The unit can prevent evaporator from freezing and maintain dehumidifying effect in low temperature environment.

When water tank is full, the water level switch will turn off the unit immediately. Make sure no water overflow from tank.

• OVERFLOW PROTECTION:

When water tank is full, the water level switch will turn off the unit immediately.

• CONVENIENT HANDLE:

You can move it conveniently.

Model No.	DP 30	DP 50
Appliance Should be Installed, Operated in a room with floor Area from:	58 m ² to 73 m ²	101 m ² to 116 m ²
Capacity:	30 L / day @ (30°C & RH=80%)	50 L / day @ (30°C & RH=80%)
Water Tank Volume:	3 Liter	6 Liter
This unit is designed to operate with a working environment at:	RH Range Manual: 35% ~ 85% Ambient Temp.: 5°C to 32°C Power Supply: 220 - 240 Volt & 50 HZ	RH Range Manual: 35% ~ 85% Ambient Temp.: 5°C to 32°C Power Supply: 220 - 240 Volt & 50 HZ
Production Country:	China	China
Weight:	18 KG	20 KG
Dimensions:	386 x 260 x 500 mm	392 x 282 x 616 mm





**DN
DEHUMIDIFIER**

PRODUCT FEATURES & DESCRIPTION

- **COMFORT**

- **LOW-NOISE DESIGN:**

Minimize noise and maximize comfort by optimizing the refrigeration and air duct systems. Noise is as low as 45dB.

- **AUTO-DEFROSTING FUNCTION:**

The unit can prevent evaporator from freezing and maintain dehumidifying effect in low temperature environment.

When water tank is full, the water level switch will turn off the unit immediately. Make sure no water overflow from tank.

- **AUTOMATICALLY CONTROLS ROOM HUMIDITY**

- **AUTO RESTART:**

If the unit breaks off unexpectedly due to the power cut, it will restart with the previous function setting automatically when the power resumes.

- **OVERFLOW PROTECTION:**

When water tank is full, the water level switch will turn off the unit immediately.

- **CONVENIENT HANDLE:**

You can move it conveniently.

Model No.	DN 12
Appliance Should be Installed, Operated in a room with floor Area from:	20 m ² to 35 m ²
Capacity:	12 L / day
Water Tank Volume:	2.1 Liter
This unit is designed to operate with a working environment at:	RH Range Manual: 35% ~ 85% Ambient Temp.: 5°C to 32°C Power Supply: 220 - 240 Volt & 50 HZ
Production Country:	China
Weight:	12.5 KG
Dimensions:	320 x 215 x 420 mm





PRODUCT

FEATURES & DESCRIPTION

- **COMFORT**
- **LOW-NOISE DESIGN:**
Minimize noise and maximize comfort by optimizing the refrigeration and air duct systems. The noise is as low as 39dB.
- **AUTO RESTART:**
If the unit breaks off unexpectedly due to the power cut, it will restart with the previous function setting automatically when the power resumes.
- **CONVENIENT HANDLE:**
You can move it conveniently.
- **SMART DEHUMIDIFICATION:**
Automatically control room humidity in a comfortable range of 45% ~ 55% according to room temperature, inhibiting bacterial growth.

Model No.	DF 20
Appliance Should be Installed, Operated in a room with floor Area from:	37 m ² to 52 m ²
Capacity:	20 L / day
Water Tank Volume:	3 Liter
This unit is designed to operate with a working environment at:	RH Range Manual: 35% ~ 85% Ambient Temp.: 5°C to 32°C Power Supply: 220 - 240 Volt & 50 HZ
Production Country:	China
Weight:	16 KG
Dimensions:	350 x 245 x 510 mm





☎ 19111



